

Select Specifications

Product Name		Sech	Drei
VLT	Single	59%	35%
	Dual	54%	31%
VLR	Single	8%	12%
	Dual	12%	12%
SC	Single	0.54	0.35
	Dual	0.62	0.48
SHGC	Single	0.46	0.3
	Dual	0.54	0.42
IR Rej	Single	83%	98%
	Dual	83%	98%
UV Rej	Single	99.9%	99.9%
	Dual	99.9%	99.9%
TSER	Single	54%	70%
	Dual	46%	58%
Glare Red	Single	34%	61%
	Dual	41%	64%
	Single	1.06	1.04
	Dual	0.48	0.47

VLT – Visible Light Transmission

VLR – Visible Light Reflection

SC – Shading Coefficient

SHGC – Solar Heat Gain Coefficient

IR Rej – Infrared Rejection

UV Rej – Ultraviolet Rejection

TSER – Total Solar Energy Rejected

Glare Red – Glare Reduction

Performance data is based on this film being applied to the inside of 3mm clear glass. All data calculated using the definitions and equations in ISO9050 & ASHRAE Handbook. The data is subject to variations within industry standards.

Copyright © 2010 Huper Optik® USA (www.huperoptikusa.com) 5821 W. Sam Houston Pkwy. N., Ste. 400, Houston, TX 77041 Phone: 888-296-3456; Fax: 832-467-1190, info@huperoptikusa.com

